




CLEAR MOULD PROTECTIVE TRANSPARENT, COMPLETE ANTI-CORROSION PROTECTION



CLEAR MOULD PROTECTIVE has been specially formulated for application to mould surfaces after their use to remove any surface moisture and to protect the mould against corrosion during storage.

APPLICATIONS

A clear, non-silicone, protective coating for use on moulds and other metallic parts and components. The transparent, dry film is non-staining and is highly recommended for use with white or clear polymers. The film will not harden or crack and is easily 'moulded-off' when recommencing production. Alternatively, the film can be easily removed using Ambersil Mould Cleaner or Amberklene FE10, ME20 or L030.

Apply an even coating to all surfaces to be protected from 9" - 12" (25 - 30cm). Ensure that the surfaces have cooled to below 35°C to ensure optimum film formation.

ADVANTAGES

Clear, Non-Staining Film	:	Will not mark or stain mouldings Highly recommended for clear and white polymers
Dry Film	:	Will not penetrate or creep into mould tool
Film Allows Subsequent Handling	:	Resists Acid Finger Marking
Resists Corrosion	:	The mould tool remains in top condition
Easily Moulded Off	:	Ensures quick start up

AREAS OF USE

All injection mould tools, blow mould tools, extrusion dies and metal components requiring corrosion protection.

TECHNICAL DATA

Appearance	:	Clear, colourless liquid
Protection against corrosion	:	TBA
Water displacing	:	TBA
Salt spray test	:	TBA
Film forming properties	:	A continuous, homogenous film

		remains after 10 minutes
Solubility	:	Soluble in solvents, insoluble in water
Flammability	:	Classified as extremely flammable under Current EC Regulations
Flashpoint	:	Not applicable in sealed aerosol
Packaging	:	400 ml aerosol (12 per carton)

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: www.ambersil.com

E-mail: sales.uk@crcind.com

Version: 2

Created: November 2011