

Technical Data



EJECTOR PIN LUBRICANT **MOULD TOOL LUBRICANT**



EJECTOR PIN LUBRICANT is a unique blend of highly refined mineral oils, extreme pressure additives and de-watering and anti-corrosion agents.

Specifically developed for use on Ejector Pins and Locator Plugs, where a long lasting, high cling release film is required.

APPLICATIONS

The heavy duty lubricating film offers outstanding performance under conditions of extreme pressure and loading on all moving and mechanical parts.

Presented as a completely clear, hard-working film, Ejector Pin Lubricant is non-staining and will not fling off the moving part and is not displaced under high pressure/load operating conditions.

Apply directly onto the part to be treated. The residual film will displace moisture and provide excellent lubrication and protection against corrosion.

TECHNICAL DATA

Appearance	: Clear, oily liquid
Odour	: Characteristic hydrocarbon
SG @ 25°C	: 0.665
Pressure @ 25°C	: 3 Bar0.
Discharge rate	: 0.89 g/sec
Temperature Range	: Operational up to 120°C
Solubility	: Soluble in hydrocarbon solvents, insoluble in water
Recommended Solvents	: Ambersil Mould Cleaner, Amberklene FE10, ME20 or LO30
Flammability	: Classified as extremely flammable under current EC Regulations
Packaging	: 400 ml aerosol (12 per carton)

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: www.ambersilindustrial.com

E-mail: sales.uk@crcind.com